



#820 INDICATOR

STANDARD FEATURES:

- Weight Display: Six Large High Contrast 7 segment red numerals for weight.
- Data Display: 128 x 64 graphic display, white/blue
- Configurable Analog/Digital converter.
- Power for (2) 350 ohm load cells.
- Readout: g, kg, oz, lb
- NEMA 4X Stainless Washdown Enclosure
- Two independent RS232/RS485 communication ports
- Piezoelectric pushbutton operation
- Programmable for ticket printing or other control operations
- Ethernet communication
- Graphical User Interface
- RFID reader in front panel
- CERTIFICATIONS: OIML and NMFS certification pending.
- SOFTWARE: Remote web access and display
- USAGE: Marine Scale and Factory Bench Scale



- MOTION COMPENSATION: True reference load cell Motion Compensation with proprietary software.
- COMPATIBLE with any Ryco, Marel, Scanvegt, Rice Lake or similar scale base.

SPECIFICATIONS:

POWER:
115/230VAC 50/60HZ

CIRCUIT PROTECTION:
ESD, EMI, RFI Protection

OPERATING TEMPERATURE:
-10°C TO 40°C

RESOLUTION:
Internal: 24 bits
Display: 25,000 divisions

SERIAL OUTPUT:
RS232, all common protocols.

WEIGHT:
2.9kg (6.4lb)

MEASUREMENT RATE:
Up to 0.01 second

STATUS INDICATORS:
Zero center, tare, net, lb, kg, oz, g

RATING/MATERIAL:
Enclosure: NEMA 4X
Heavy stainless steel

RESPONSE TIME:
0.25 seconds

APPROVALS:
OIML PENDING
UL

WARRANTY:
Two Year limited warranty